



SYNTHETIC SAE 5W30 SN PLUS

DESCRIPTION:

Synthetic SAE 5W30 Motor Oil provides high quality engine protection under all driving conditions and is formulated with full synthetic base stocks and a premium additive package to provide extra protection against the harmful effects of city driving, where cars undergo a higher stress due to constant stopping and going.

Synthetic SAE 5W30 Motor Oil low friction formula helps improve gas mileage for long engine life and helps protect against rust, corrosion, startup wear, varnish build-up, and eliminates the need for extra oil additives. It also protects against thermal breakdown which helps prevent stuck rings. Specially formulated to protect high compression gasoline direct injection engines from the occurrence of Low Speed Pre-Ignition (LSPI) and Timing Chain Wear.

FEATURES/BENEFITS:

- Combats Low Speed Pre-Ignition (LSPI)
- Protects engines under all driving conditions
- Lowers friction and improves gas mileage
- Provides longer engine life
- Protects against rust, corrosion and varnish
- Resists thermal break-down

APPLICATIONS:

Synthetic SAE 5W30 Motor Oil meets requirements of API SN PLUS service. **Synthetic SAE 5W30 Motor Oil** meets or exceeds the demanding requirements of International Lubricant Standardization and Approval Committee (ILSAC) GF-6 (Use ILSAC GF-6 where GF-1 through GF-5 are recommended). ILSAC GF-6 comprises the latest standard for passenger car, van, light truck and sport utility vehicles motor oils. This product is also recommended for older engines, which owner's manual calls for API SN PLUS, SN, SM, SL, SG, SF/RC Service Classifications or any combination thereof. Viscosity recommendations vary according to temperature and engine manufacturer. Suitable for Toyota, Honda, and Mazda.

Meets Performance Requirements:

- GM 6094M (for GM vehicles produced prior to 2011)
- Honda/Acura HTO-06
- Chrysler MS6395
- Chrysler MS6395V
- Ford WSS-M2C946-A

* ALWAYS CONSULT YOUR OWNER'S MANUAL FOR THE PROPER FLUID FOR YOUR EQUIPMENT.

TYPICAL TEST DATA

SAE GRADE	5W30
Specific Gravity, (60°F)	0.8490
Viscosity, @ 40°C, cSt	59.6
Viscosity, @ 100°C, cSt	10.3
Viscosity Index	163
Cold Crank, cP at -30°C	4,560

Flash Point, °F	457
Pour Point, °C (°F)	-39 (-38)
Noack Volatility %	8
High Temp/High Shear Visc, cP @150°C	3.1
Color	2.5
Phosphorus, wt%	0.078
Zinc, wt%	0.088

Typical test data are average values only. Minor variations which do not affect product performance are to be expected during normal manufacturing.

F-140

6-16-2018

REV 7